



SWING-AWAY AMP

SWING-AWAY AMP HARDWARE

Hardware allows for fast and simple swing away and removal.

Swing away feature allows patients to be easily transferred in and out of a wheelchair.

Pad can be easily removed from and reinstalled onto wheelchair.



VERTICAL ADJUSTABILITY

Toggle lever allows positioning at multiple angles.

Up to 4" of height adjustment to accommodate varying seat cushion thicknesses.

Pad can be adjusted 3" in depth to accommodate wheelchair depth conversion kits.



Designed to install on all popular wheelchairs within minutes.

Provides patients a fully adjustable amputee support that will coincide with any wheelchair cushion.

Allows patients to be transferred in and out of a wheelchair within seconds.

Installs onto either left or right side of wheelchair.

Fits tubing sizes from 7/8" to 1".

Amputee pad has adduction to help center residual limb.

10" SWING AWAY AMP PART NUMBERS

Width x Length	Thickness	Extension Kit
8" X 10"	3"	AMPSA810
9" X 10"	3"	AMPSA910
10" X 10"	3"	AMPSA1010
11" X 10"	3"	AMPSA1110
12" X 10"	3"	AMPSA1210

14" SWING AWAY AMP PART NUMBERS

Width x Length	Thickness	Extension Kit
8" X 14"	3"	AMPSA814
9" X 14"	3"	AMPSA914
10" X 14"	3"	AMPSA1014
11" X 14"	3"	AMPSA1114
12" X 14"	3"	AMPSA1214

COMFORT-TEK

*See page 3 for details.

