

Our new Journey® lift is an ultra compact, portable folding standaid with best-in-class functionality. It is compact and lightweight allowing caregivers to maneuver in tight spaces while folding for easy storage or transportation. The first on the market adjustable cow-horn mechanism supports a range of patient heights and sizes, allowing your facility to have one lift that meets the needs of many. Our careful attention to product design with the Journey ensures that both the caregiver's and the resident's needs have been met.



Smart Monitor



The unique Smart Monitor control box is programmable and will accurately record and display vital lift utilization and service data. An easy to read LCD display provides the valuable information at the touch of a button.



Unique Folding Design

The Journey's unique folding design stands unaided for easy storage. The compact design also provides an ideal size for transporting. It is the only standaid on the market that folds.



Adjustable Cow-Horn

The unique adjustable cow-horn mechanism supports a range of resident heights and sizes. It is also ideal for transfers from low chairs.



Adjustable Kneepad

The sculpted kneepad is easily adjusted for ultimate patient comfort. Adjustable with one hand.

SPECIFICATION

	IMPERIAL	METRIC
Safe Working Load	341 lbs	155 kgs
Maximum Overall Length	39.4"	1000 mm
Minimum Overall Length	36.8"	935 mm
Maximum Overall Height	63.0"	1600 mm
Minimum Overall Height	44.5"	1130 mm
Maximum Height to Attachment Point	60.2"	1530 mm
Minimum Height to Attachment Point	28.4"	720 mm
Turning Radius	45.1"	1145 mm
Legs Open - External Width	38.2"	970 mm
Legs Open - Internal Width	34.5"	875 mm
Legs Closed - External Width	27.0"	685 mm
Legs Closed - Internal Width	22.2"	590 mm
Widest Point (between support handles)	18.8"	475 mm
Overall Height of Legs	4.3"	110 mm
Ground Clearance	1.2"	30 mm
Front Twin Casters	3.0"	75 mm
Rear Braked Casters	4.0"	100 mm

WEIGHTS

	IMPERIAL	METRIC
Mast, Base & Boom Assembly	82.4 lbs	37.4 kg
Power Pack	6.2 lbs	2.8 kg
Total	88.6 lbs	40.2 kg
Base Assembly (not incl. battery)	30.2 lbs	13.7 kg
Mast & Boom (not incl. battery)	42.3 lbs	19.2 kg
Foot Tray	9.9 lbs	4.5 kg

ELECTRIC SHOCK PROTECTION

Charger – Class II
Lift – Internal power source

DEGREE OF SHOCK PROTECTION

Charger – Type B
Lift – Type B
Intended operating environment: >+5°C <+40°C
Outside this environment functionality and safety may be compromised

ELECTRICAL SPECIFICATIONS

Battery – 24vDC rechargeable sealed lead acid type
Battery capacity – 3.2A Ampere hours
Charger rated input – 100-240V AC 24 VDC 50/60Hz
Charger rated output – 29.5 VDC, Max. 19 W