

# Rexx and Fast Rexx

A favorite Q-Series design available in two distinct models



- The Rexx which rises from 7-7/8" low to 26" high
- The fast-rising Fast Rexx which rises from 7-7/8" to 28" high in 20 seconds

The Fast Rexx meets OSHA speed recommendation of 20 seconds; can be expected to reduce staff injuries related to stooping and lifting, increase staff productivity and reduce staff turnover rates.

**Q-Series**  
Quality. Detail. Value.



Standard Pendant Controller with  
Optional Foot-end Control



Rexx model

Height Floor to Mattress Support	7-7/8" - 26" (28" Fast Rexx)
Deck Angles - Back Elevation	0 - 70°
Deck Angles - Knee Elevation	0 - 20°
Bed Length - Overall Length	84-1/2" / 88-1/2"
Bed Length - Sleep Surface	76" / 80"
Bed Width - Sleep Surface	35"
Weight of Bed (without accessories)	170 lbs / 78 kg
Safe Working Load	450 lbs / 204 kg

Item #	Description
QD2000B	Rexx bed
QD2250B	Rexx Fast bed
Q6663	Swivel/locking 360° bed casters
Q6674	Foot end control - Rexx
Q6607	Foot end control - Fast Rexx
RM930	Three position pivot assist rail - universal
RM950	Fixed assist rail - universal
RAD306H	Standard 1/2 head end side rail - set
RR501	3/4 length collapsible side rails
Q6412LP	Rexx side rail mount pendant holder
Q6414LP	Rexx gooseneck pendant holder - side rail mount
Q6416LP	Rexx plastic pendant holder - head/foot board mount
Q6417LP	Rexx gooseneck pendant holder - board mount
Q6730	Universal trapeze bar
Q6733	Advantage trapeze mounting frame
Q6584	Fast Rexx pendant holder - side rail mount
Q6591	Fast Rexx gooseneck pendant holder - side rail mount
Q6589	Fast Rexx plastic pendant holder - head/foot board mount
Q6590	Fast Rexx gooseneck pendant holder - board mount



For ordering and technical support on beds, accessories and furniture, call: